# Fusion Cool 2269

## PREMIUM SEMI-SYNTHETIC METALWORKING FLUID

ISO: 9001:2015 CERTIFIED

### PRODUCT DESCRIPTION

Fusion Cool 2269 is a high performance semi-synthetic coolant for machining and grinding of ferrous and non-ferrous alloys. Fusion Cool 2269 is formulated with a unique blend of raw materials that give this product exceptional biostability.

### BENEFITS

- Versatile – Used in variety of applications.
- Excellent Corrosion Protection
- Safe and Mild.
- Long Sump Life- Biostatic
- Good lubricity.
- Cleanliness
- Nitrite free.

### APPLICATION

| | |
|---|---|
| Honing, Tapping, Reaming | 5-10% |
| Milling, Drilling, Turning | 5-10% |

### REFRACTOMETER READING

| | |
|---|---|
| 2% | 1.2 |
| 4% | 2.4 |
| 6% | 3.6 |
| 8% | 4.8 |
| 10% | 6.0 |

### AVAILABILITY

- 5 gallon pails
- 55 gallon drums
- Tote Tanks
- Bulk shipments.

### TYPICAL PHYSICAL PROPERTIES

| | |
|---|---|
| Concentrate Appearance | Amber |
| Density (pounds/gallon) | 8.5 |
| Flash Point (C.O.C.) | None |
| pH @ 10% | 9.2 |
| Odor | Bland |
| Residue | Liquid Film |
| Metal Compatibility | All metals |

### STORAGE AND HANDLING

Fusion Cool 2269 can be stored either indoors or outdoors. If outdoor storage is used, the product should be brought to room temperature prior to use. Product is not for internal consumption. Fusion Cool 2269 is non-irritating and non-toxic when used properly.

### DISPOSABILITY

Non-biodegradable material must be removed prior to disposal. Conventional waste treatment methods such as acid-alum-polymer chemical treatment or ultrafiltration can be used to meet local, state, and federal requirements:

### ADDITIONAL INFORMATION

A MSDS for this product is available upon request. Purchasers of this product are urged to review and retain this information. For additional information, evaluation samples or price quotations, please contact:


### FUSION CHEMICAL

99 E. JOE ST.

HUNTINGTON, IN. 46750

260-443-1154